

**Electrical:**

- 1.Voltage Rating: 125 Vac Rms
- 2.Current Rating: 1.5 Amp
- 3.Contact Resistance: 40 Milliohms Max
- 4.Insulation Resistance: 1000 Megohms Min@500 Vdc
- 5.Dielectric Strength: 1000 Vac Rms 60Hz,1Min

**Mechanical:**

- 1.Operating: 750 Cycles Min

**Environmental:**

- 1.Storage: -40°C To +85°C
- 2.Opertion: -20°C To +75°C

Mates With Modular Plug Conforming To FCC Part 68,Subpart F


**Notes:**

**MATERIALS**

**HOUSING:** HIGH TEMP. THERMOPLASTIC FLAMMABILITY UL 94V-0

**CONTACTS:** PHOSPHOR BRONZE

**PLATING:** GOLD PLATING OVER NICKEL IN CONTACT  
TIN PLANTING OVER NICKEL IN SOLDER AREA

TOLERANCE UNLESS OTHERWISE SPECIFIED		CUSTOMER COPY			Coorle Technology				
LINER	ANGLES	PROJECTION 			PROD. TOP ENTRY PCB JACK		DESCRIP. (4P4C SMT 无台阶)		
0 ± 0.50	± 3'				PROD. NUMBER				
.0 ± 0.38		DESIGN	PAUL HUANG	6/15/19	UNIT	SCALE	SIZE	REV.	<a href="http://www.coorle.com">Http://www.coorle.com</a> Tel: 0769-81585156 Fax: 0769-81605156
.00 ± 0.25		APPRO.			MM	/	A4	C	

**ROHS**