



备注:

1. 外壳材料: 铁料 (SPCC) 外表层镀金
2. 主体材料: LCP胶料
3. 端子材料: 青铜 (C2680) 接触点刷镀金 1U,

NOTE :

1. SPECIFICATION:
 - 1.1. CURRENT RATING: 0.5 Amp Max.
 - 1.2. VOLTAGE RATING: 40 V ac(r.m.s) Max.
 - 1.3. CONTACT RESISTANCE: 10m ohms Max.mated
 - 1.4. INSULATION RESISTANCE: 100M ohms Min.
 - 1.5. DIELECTRIC WITHSTANDING VOLTAGE: AC 500V Min. (for 1 minute)
 - 1.6. OPERATION TEMPERATURE RANGE: -25°C~85°C
2. MECHANICAL
 - 2.1 INSERTION FORCE: 4.5KGF MAXMUM
 - 2.1 WITHDRAWAL FORCE: 1.0KGF MINIMUM; 4.0KGF MAXMUM

成品图 MANUFACTURE DWG				库乐科技			
公差一览表 TOLERANCE UNLESS OTHERWISE				单位 UNITS	制图 DRAWING	客户料号 CUSTOMER PART NO.	
.X	±0.15	.X'	±5°	比例 SCALE	审核 CHKD	产品名称 PRODUCT NAME	
.XX	±0.10	.XX'	±2°	日期 DATE	核准 APPD	角法 VIEW	版本 VER
.XX	±0.08	.XX'	±1°				
.XXX	±0.03	.XXX'	±0.5°				