

NOTES:

ELECTRICAL:


- 1. VOLTAGE RATING : 125 VAC RMS.
- 2. CURRENT RATING : 1.5 AMP.
- 3. CONTACT RESISTANCE : 30 MILLIOHMS MAX.
- 4. INSULATION RESISTANCE : 500 MEGOHMS MIN @ 500 VDC.
- 5. DIELECTRIC STRENGTH : 1000 VAC RMS 50Hz or 60Hz, 1MIN.

MECHANICAL:

- 1. HOUSING & INSERT MATERIAL : PBT UL94V-0.
- 2. CONTACT MATERIAL : PHOSPHOR BRONZE T=0.35MM.
- 3. SHIELD : 0.20 ~ 0.25MM THICKNESS BRASS WITH TIN PLATED.
- 4. PLATING : 1. CONTACT AREA-SELECTIVE GOLD PLATING.
2. TAILS PLATING TIN OVER NICKEL.
- 5. MATING/UNMATING FORCE : 2.2KG. F MAX.
- 6. RETENTION STRENGTH : 7.7KG. F MIN BETWEEN JACK AND PLUG.
- 7. OPERATING LIFE : 600 CYCLES MIN.

ENVIRONMENTAL:

- 1. STORAGE : -10°C ~ +40°C RELATIVE HUMIDITY<70%.
- 2. OPERATION : -40°C ~ +70°C.



© 库乐科技

UNIT :mm

.xx +/-0.25, .xxx +/-0.13

Approved By: JP. Gong

1X1 SMT RJ45

REV.
D

Drafted by:JG. CHEN

SHEET 1 OF 1